



TECHNICAL DATA: #MAA9113 GENERAL PURPOSE MASKING TAPE

Product Description:

#MAA9113 General Purpose Masking Tape paper-backed tape with rubber latex adhesive on a single side.

Physical Properties:

Product Code	Test Method	#MAA9113
Total Thickness, Microns	GB/T 7125-2014	120-130
Ball Tack	GB/T 4852-2002	≥5
180° Peel Strength (to stainless steel) N/IN	GB/T 2792-2014	≥6
Tensile Strength N/IN	GB/T 30776-2014	≥60
Elongation %	GB/T 30776-2014	6-10
Holding Power, hour	GB/T 4851-2014	10
Max Temperature, °C	-	60°C/60min

Features:

- Water-resist, quick stick, easy peel and easy tear
- Colour: White, off-white, yellow
- Meet RoHS Requirement

Application:

Widely used for indoor and outdoor painting masking for the wood, furniture, metal, decoration, and plastic parts surface.

Storage & Usage:

1. Tape jumbo rolls should be placed vertically in well packages and avoid being pressed against the glue surface
2. Clean and dry in a well-ventilated area, preferably at a temperature between 20°C and 30°C. Away from direct sunlight, freeze and other heat sources
3. Tape should be used within 7 months from the date of production

Note: All information and recommendations are given by us in good faith based on practical experience but without warranty. The user shall determine the suitability of the product and the method of application for each specific use.