



TECHNICAL DATA: REINFORCED ALUMINUM TAPE

Product Description:

3-way Foil-Scrim-Kraft backing, combined with a transparent high-performance synthetic rubber-resin adhesive, protected by an easy-release silicone release paper

Physical Properties:

Product Code	Reference Value	Test Value
Testing Environment	T=23°±2°, RH=65%±10%	T=23 °C, RH=60%
Appearance	Level off, without loose volume, no crack	Level off, without loose volume, no crack
Total thickness (mm)	0.23 ± 0.01	0.23
180° peel adhesion	≥20	Base tearing
Tensile Strength	≥60	71.9

Features:

- Reinforced Aluminum foil backing with Synthetic rubber Adhesive/Silicone Release Paper
- Colour: Silver
- Meet RoHS Requirement

Application:

High-grade foil tape. Excellent for sealing joints and seams of foil-faced insulation materials. Good for refrigerator industry metal patching and air conditioners. The surface must be clean and free from dust and grease

Storage & Usage:

1. Tape jumbo rolls should be placed vertically in well packages and avoid being pressed against the glue surface
2. Clean and dry in a well-ventilated area, preferably at a temperature between 20°C and 30°C. Away from direct sunlight, freeze and other heat sources
3. Tape should be used within 7months from the date of production

Note: All information and recommendations are given by us in good faith based on practical experience but without warranty. The user shall determine the suitability of the product and the method of application for each specific use.