



TECHNICAL DATA: #A120 ALUMINUM FOIL TAPE

Product Description:

#A120 Aluminium Foil Tape is a soft Aluminium foil coated with Rubber Resin pressure-sensitive adhesive for excellent adhesion and self-wound on a release liner

Physical Properties:

Product Code	Test Method	#A120
Film Thickness		25 microns
Total thickness		55 microns
Pure Aluminum Foil Thickness, S	GB/7/125-1999	2
Ball Tack, #	-	-
180° peel adhesion to stainless steel, N/IN	GB/2792-1998	≥14
Tensile strength, N/IN	GB/7753-1987	≥22
Elongation, %	-	-

Features:

- Synthetic rubber Adhesive/Silicone Release Paper
- Colour: White
- Meet RoHS Requirement

Application:

High-grade foil tape. Excellent for sealing joints and seams of foil-faced insulation materials. Good for refrigerator industry metal patching and air conditioner

Storage & Usage:

1. Clean and dry in a well-ventilated area, preferably at a temperature between 20°C and 30°C. Away from direct sunlight, freeze and other heat sources
2. Tape should be used within 7months from the date of production

Note: All information and recommendations are given by us in good faith based on practical experience but without warranty. The user shall determine the suitability of the product and the method of application for each specific use.