



TECHNICAL DATA: ALUMINUM GLASS TAPE

Product Description:

Aluglass tape is an Aluminium glass cloth back tape and mesh glass cloth which is merged with high-performance hot melt adhesive and finally given protection by silicone release paper

Physical Properties:

Product Code	Reference Value	Aluminum Glass Tape
Testing Environment	T=23±2, RH=65%±10%	T=23°C, RH=60%
Appearance	Level off, without loose volume, no crack	Level off, without loose volume, no crack
Total thickness (mm)	0.23±0.01	0.239
180° peel adhesion	≥14	18.56

Features:

- Aluminum foil backing with synthetic rubber adhesive/Silicone release paper
- Colour: Silver
- Meet RoHS Requirement

Application:

High-grade foil tape. Excellent for sealing joints and seams of foil-faced insulation materials. Good for refrigerator industry metal patching and air conditioners. The surface must be clean and free from dust and grease

Storage & Usage:

1. Clean and dry in a well-ventilated area, preferably at a temperature between 20°C and 30°C, away from direct sunlight, freeze and other heat sources
2. Tape should be used within 7 months from the date of production

Note: All information and recommendations are given by us in good faith based on practical experience but without warranty. The user shall determine the suitability of the product and the method of application for each specific use.