



## TECHNICAL DATA: #B155A SOLVENT BASED BOPP TAPE

### **Product Description:**

#B155A OPP Packaging Tape is made of double-directions pull bi-oriented polypropylene film backing with solvent acrylic emulsion adhesion

### **Physical Properties:**

| Product Code                          | Test Method  | # B155A                  |
|---------------------------------------|--------------|--------------------------|
| Tape Thickness, Microns               | GB/7125-1999 | 55±2                     |
| Backing                               | -            | BOPP Film                |
| Adhesive Type                         | -            | Solvent Acrylic Emulsion |
| 180° Peel Strength (to steel)<br>N/IN | GB-2792-1998 | ≥6                       |
| Tensile Strength N/IN                 | GB/7753-1987 | ≥60                      |
| Elongation %                          | ASTM D-1000  | 100                      |

### **Application:**

General industrial use, carton sealing, bundling, and packaging

### **Storage & Usage:**

1. Tape should be stored in a cool, dry, sheltered area and must avoid storage in direct sunlight.
2. Storage temperature is 20°C-30°C, Humidity: 40%-70% area
3. The application surface must be dry, clean and free of dust, oil and other such contaminants.
4. Tape should be used within 12 months of delivery

*Note: All information and recommendations are given by us in good faith based on practical experience but without warranty. The user shall determine the suitability of the product and the method of application for each specific use.*