



TECHNICAL DATA: PVC PIPE WRAPPING TAPE

Product Description:

PVC Pipe Wrapping Tape is made of soft polyvinyl chloride (PVC) film, coated with rubber pressure-sensitive adhesive and also known as identification tape, floor tape, landmark tape, etc. Warning tape has the advantages of waterproof, moisture-proof, weatherproof, anti-corrosion and anti-static, etc. It is suitable for anti-corrosion protection of air, water, and other pipelines, as well as for ground signs and warnings.

Physical Properties:

Product Code	Standard	Unit	Test Method
Material type	PVC	-	-
Glue type	Natural rubber	-	-
Total thickness	0.130±0.01	mm	ASTM D1000
Initial tack	≥10	#	GB/T 4852-2002
Adhesion to steel	≥2/25	N/mm	ASTM D1000
Tensile strength	≥40/25	N/mm	ASTM D1000
Elongation	≥130	%	ASTM D1000
Application temperature	10-40	°C	-
Service temperature	0-60	°C	-

Features:

- Colour: White, black

Application:

- Ideal for underground pipeline or conduit corrosion, air conditioning duct wrapping, moisture proofing and industrial pipe wrapping

Storage & Usage:

1. 12 months when stored at 15-30 °C (59-86F) / below 70% relative humidity out of direct sunlight
2. It is essential, as with all pressure-sensitive tapes, that the surface to which the tape is applied must be clean, dry, free of grease, oil or other contaminants

Note: All information and recommendations are given by us in good faith based on practical experience, but without warranty. The user shall determine the suitability of the product and the method of application for each specific use