



TECHNICAL DATA: # SELF-ADHESIVE REINFORCED KRAFT PAPER TAPE

Product Description:

Packaging Tape is a fast, reliable, economical, pressure-sensitive and self-adhesive packaging kraft tape that improves the efficiency of your packaging line. With strong initial adhesion and a strong seal, the unique gripper rib technology gives this tape better tensile strength than ordinary tape and is less prone to theft.

Physical Properties:

Product Code	Standard	Metric	Test Method
Color	Natural		
Composite Layer	Polymeric copolymer		
Adhesion	Hot Melt Adhesive		
Total thickness	6.3 mils	0.16mm	ASTM D - 3652
Peel Adhesion 90°	90 oz/in	25 N/25mm	ASTM D - 3330
Holding Power	>24 h	>24 h	ASTM D – 3654
Tensile Strength	45 lbs/in	200 N/25mm	ASTM D-3759
Elongation at Break	3-5%	3-5%	ASTM D-3759
Service Temp. Mini	23°F	-5°C	BC/BD-220SE
Service Temp. Max	23°F	60°C	DHG – 9055A
Backing	70 g/m2 Kraft paper		
Reinforcement MD	72mm (1-1-1-1-1) Fibreglass		
Reinforcement CD	28mm G150(1-1-1) Fiberglass Diamond Pattern		
Base material	Top and bottom ply: 25 lb (40g/m2) Kraft paper		

Application:

Mainly used for international shipping packaging where high environmental standards are required, suitable for cartons' sealing and special packaging.

Storage & use:

Tear off the tape and use it to seal the top and bottom of the cardboard box. Suitable for all types of cardboard boxes. It's recommended to store it in a clean and dry place. Damaged packaging shall be prevented and not stored with volatile solvents. The storage temperature shall be 4°C to 26°C, and the humidity shall be between 40% and 50%. Rotate inventory recommended.

Note: All information and recommendations are given by us in good faith based on practical experience, but without warranty. The user shall determine the suitability of the product and the method of application for each specific use